

# 30SR-2

# KOBELCO®

*Your competitive edge.*

<b>30SR-2</b>	
<b>WT</b>	6,922 lbs
<b>HP</b>	22.7 SAE NET@ 2300 RPM
<b>BKT CAP</b>	2.13-4.25 cu ft.

## STANDARD EQUIPMENT

- "Zero tail swing" counterweight does not extend beyond track width when swung over either side
- Rubber-tracks
- Combined single or bi-directional auxiliary hydraulics with piping & control
- Swing boom - 60° right 70° left
- Yanmar 3TNE82A 4 cycle, 3 cylinder water cooled swirl chamber diesel engine 22.7 @ 2300
- ROPS/FOPS 4 post canopy
- Arm rests
- Adjustable, cushioned and weatherproof operator seat
- Glow plugs starting aid
- 3'11" arm
- Two axial piston type hydraulic pumps 2 x 8.2 gal/min
- Dozer/swing pump: fixed gear 1 x 6.4 gal/min
- Pilot pump: fixed gear 1 x 3.1 gal/min
- Two speed travel 2.8/1.6 mph switch on travel lever
- Full hydrostatic drive system (2 axial piston motors)
- Track tension adjustment (grease type)
- 12V electrical starting system. Includes heavy duty battery and starting motor
- Air cleaner (dry type) with indicator for replacement
- Hydraulic oil filter
- One touch engine decel
- Parking brake, automatically applied and released
- Two level control for arm, boom, bucket and swing
- Operator control pattern charger (ISO/TLB)
- Pilot operated wrist controls and foot pedals
- Fuel tank: 10 gal
- Display includes: engine oil pressure lamp, water temperature guage, fuel guage, hour meter, battery charge lamp, travel speed indicator lamp, air restritor warning lamp
- Hydraulic dozer blade
- Operator's manual storage compartment
- Hinged engine cover
- Removable engine access cover below operator seat
- Right and left hinged access covers
- Sealed and lubricated track rollers
- Electric horn

## OPTIONAL EQUIPMENT

- ROPS/FOPS cab w/ heater
- Steel tracks
- Buckets
- Travel alarm

NOTE: Due to our policy of continual product improvement, all designs and specifications are subject to change without advance notice.



# 30SR-2

# KOBELCO®

*Your competitive edge.*

### Sales & Product Support Offices

12755 S. Kirkwood Drive  
Stafford, Texas 77477 USA

Phone: 281.240.4800

Fax: 281.240.4906

Website: [www.kobelcoamerica.com](http://www.kobelcoamerica.com)

E-Mail: [digin@kobelcoamerica.com](mailto:digin@kobelcoamerica.com)

Bulletin No. 30SR-2-US-10/02-7.10M-PERF-103

### Headquarters & Manufacturing

501 Richardson Rd.  
Calhoun, Georgia 30701 USA

Phone: 706.629.5572

Fax: 706.629.3952

© Kobelco Construction Machinery America LLC

## 30SR-2

### SHORT RADIUS Compact Excavator

